

Contact-Cooled Rotary Screw Air Compressors

R-Series 90-160 kW (125-200 hp) 60 Hz

Ingersoll Rand R-Series compressors offer the highest levels of reliability, efficiency and productivity with time proven designs and advanced technologies.



- **Progressive Adaptive Control (PAC) Protection** continuously monitors key operating parameters and adapts to prevent unexpected downtime.
- **V-Shield Technology** provides a totally integrated, leak-free design.

- **Sequential Cooling System** significantly improves efficiency, serviceability and noise level.
- **Time-Proven Airends** provide market-leading efficiency and reliability.
- **Trouble-Free Operation** ensures increased uptime with features such as two-stage filtration, easy maintenance and extended life Ingersoll Rand premium grade coolant.

■ **The Xe-Series Controller**

- Features large navigation buttons and an intuitive, high resolution color display for easy compressor control.
- Provides web-enabled communication and control with email notification of warnings and trips.



Xe-145M option shown

Standard Features include:	Optional Features include:
Xe-90M Controller with 90 mm screen	Xe-145 controller with 145 mm screen
Progressive Adaptive Control (PAC™) Protection	Flow control by inlet modulation
Air-cooled sequential cooling system	Low ambient protection to -23°C (-10°F)* & frost protection to -10°C (14°F)
V-Shield™ technology	High ambient protection up to 55°C (131 °F)
Ergonomic swing-out lid on separator tank	Premium high dust filtration (inlet and package pre-filters)
Noise attenuation enclosure	Fluid containment system
Package pre-filtration	Web-based graphing and trending
Long-life filtration and separation elements	Email notification of warnings and trips
12-month full package warranty	Energy Recovery System (ERS)
	Outdoor modification/rain protection

* Available in North America Only

i Ingersoll Rand Standard – 60 Hz Performance										
Model	Max. Pressure		Nominal Power		Capacity (FAD)*		Dimensions (Length x Width x Height)		Weight (Air-cooled)	
	bar g	psig	kW	hp	m ³ /min	cfm	mm	in	kg	lb
R90i	7.5	110	90	125	17.58	621	2,703 x 1,466 x 2,032	106 x 58 x 80	2,420	5,335
	8.5	125	90	125	16.03	566	2,703 x 1,466 x 2,032	106 x 58 x 80	2,420	5,335
	10.0	145	90	125	14.47	511	2,703 x 1,466 x 2,032	106 x 58 x 80	2,420	5,335
	14.0	200	90	125	10.19	360	2,703 x 1,466 x 2,032	106 x 58 x 80	2,420	5,335
R110i	7.5	110	110	150	21.27	751	2,703 x 1,466 x 2,032	106 x 58 x 80	2,550	5,620
	8.5	125	110	150	19.54	690	2,703 x 1,466 x 2,032	106 x 58 x 80	2,550	5,620
	10.0	145	110	150	17.70	625	2,703 x 1,466 x 2,032	106 x 58 x 80	2,550	5,620
	14.0	200	110	150	13.73	485	2,703 x 1,466 x 2,032	106 x 58 x 80	2,550	5,620
R160i	7.5	110	160	200	27.89	985	2,855 x 1,836 x 2,032	112 x 72 x 80	2,926	6,450
	8.5	125	160	200	25.63	905	2,855 x 1,836 x 2,032	112 x 72 x 80	2,926	6,450
	10.0	145	160	200	24.49	865	2,855 x 1,836 x 2,032	112 x 72 x 80	2,926	6,450
	14.0	200	160	200	19.68	695	2,855 x 1,836 x 2,032	112 x 72 x 80	2,926	6,450

ie Ingersoll Rand Premium – 60 Hz Performance										
Model	Max. Pressure		Nominal Power		Capacity (FAD)*		Dimensions (Length x Width x Height)		Weight (Air-cooled)	
	bar g	psig	kW	hp	m ³ /min	cfm	mm	in	kg	lb
R90ie	7.5	110	90	125	18.80	664	2,855 x 1,836 x 2,032	112 x 72 x 80	3,198	7,050
	8.5	125	90	125	17.41	615	2,855 x 1,836 x 2,032	112 x 72 x 80	3,198	7,050
	10.0	145	90	125	16.06	567	2,855 x 1,836 x 2,032	112 x 72 x 80	3,198	7,050
	14.0	200	90	125	13.00	459	2,855 x 1,836 x 2,032	112 x 72 x 80	3,198	7,050
R110ie	7.5	110	110	150	22.99	812	2,855 x 1,836 x 2,032	112 x 72 x 80	3,198	7,050
	8.5	125	110	150	20.53	725	2,855 x 1,836 x 2,032	112 x 72 x 80	3,198	7,050
	10.0	145	110	150	19.28	681	2,855 x 1,836 x 2,032	112 x 72 x 80	3,198	7,050
	14.0	200	110	150	15.43	545	2,855 x 1,836 x 2,032	112 x 72 x 80	3,198	7,050
R160ie	7.5	110	160	200	29.17	1,030	2,855 x 1,836 x 2,032	112 x 72 x 80	3,198	7,050
	8.5	125	160	200	27.47	970	2,855 x 1,836 x 2,032	112 x 72 x 80	3,198	7,050
	10	145	160	200	25.57	903	2,855 x 1,836 x 2,032	112 x 72 x 80	3,198	7,050
	14	200	160	200	20.53	725	2,855 x 1,836 x 2,032	112 x 72 x 80	3,198	7,050

n Ingersoll Rand Nirvana Standard – 60 Hz Performance										
Model	Max. Pressure		Nominal Power		Capacity (FAD)**		Dimensions (Length x Width x Height)		Weight (Air-cooled)	
	bar g	psig	kW	hp	m ³ /min	cfm	mm	in	kg	lb
R90n	4.5-10	65-145	90	125	8.47-18.83	299-665	2,703 x 1,466 x 2,032	106 x 58 x 80	2,060	4,540
R110n	4.5-10	65-145	110	150	8.47-21.86	299-772	2,703 x 1,466 x 2,032	106 x 58 x 80	2,060	4,540
R160n	4.5-10	65-145	160	200	8.47-28.12	299-993	2,855 x 1,836 x 2,032	112 x 72 x 80	2,363	5,210

ne Ingersoll Rand Nirvana Premium – 60 Hz Performance										
Model	Max. Pressure		Nominal Power		Capacity (FAD)**		Dimensions (Length x Width x Height)		Weight (Air-cooled)	
	bar g	psig	kW	hp	m ³ /min	cfm	mm	in	kg	lb
R90ne	4.5-10	65-145	90	125	8.86-19.54	313-690	2,855 x 1,836 x 2,032	112 x 72 x 80	2,495	5,500
R110ne	4.5-10	65-145	110	150	8.86-23.36	313-825	2,855 x 1,836 x 2,032	112 x 72 x 80	2,495	5,500
R160ne	4.5-10	65-145	160	200	8.86-30.02	313-1,060	2,855 x 1,836 x 2,032	112 x 72 x 80	2,495	5,500

*FAD (Free Air Delivery) is full package performance including all losses. Tested per ISO 1217:2009 Annex C and is measured at 0.5 bar g/10 psig lower than maximum pressure.

**FAD (Free Air Delivery) is full package performance including all losses. Tested per ISO 1217:2009 Annex C and capacity range is measured at 7 bar g/100 psig.



Ingersoll Rand, IR, the IR logo are trademarks of Ingersoll Rand, its subsidiaries and/or affiliates. All other trademarks are the property of their respective owners.

Ingersoll Rand compressors are not designed, intended or approved for breathing air applications. Ingersoll Rand does not approve specialized equipment for breathing air applications and assumes no responsibility or liability for compressors used for breathing air service.

Nothing contained on these pages is intended to extend any warranty or representation, expressed or implied, regarding the product described herein. Any such warranties or other terms and conditions of sale of products shall be in accordance with Ingersoll Rand's standard terms and conditions of sale for such products, which are available upon request.

Product improvement is a continuing goal at Ingersoll Rand. Designs, available functions and specifications are subject to change without notice or obligation.